



W5

ASFA S (12 mm) Hose Clamp AISI 316 Stainless Steel - W5

This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened.

Thanks to the combination of the housing, locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.


This clamp is especially indicated for use in the pulp and paper, maritime and foodstuffs industries.

DIN 3017. The ASFA SW5 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø										
mm	Part nº	L max.	S +0,10	h max.	a +0,3 a -0,1	b max.	Maximum values		Box Quantity (MOQ)	Outer Packing
							Torque (Nm)	Pressure (Bars)		
16-27	0301772-0	29,6	0,85	11	12,2	16,7	4,5	40	50	400
20-32	0301750-0	29,6	0,85	11	12,2	16,7	5,5	40	50	400
25-40	0301751-9	29,6	0,85	11	12,2	16,7	5,5	40	50	400
30-45	0301773-8	29,6	0,85	11	12,2	16,7	5,5	35	50	400
32-50	0301752-7	29,6	0,85	11	12,2	16,7	6,5	35	50	200
40-60	0301753-5	29,6	0,85	11	12,2	16,7	6,5	30	50	400
50-70	0301754-3	29,6	0,85	11	12,2	16,7	7	25	50	400
60-80	0301755-1	29,6	0,85	11	12,2	16,7	7	20	50	50
70-90	0301756-0	29,6	0,85	11	12,2	16,7	7	17	50	50
80-100	0301757-8	29,6	0,85	11	12,2	16,7	7	14	25	200
90-110	0301758-6	29,6	0,85	11	12,2	16,7	7	12	25	200
100-120	0301759-4	29,6	0,85	11	12,2	16,7	7	10	25	200
110-130	0301760-7	29,6	0,85	11	12,2	16,7	7	8	25	25
120-140	0301761-5	29,6	0,85	11	12,2	16,7	7	7	25	25
130-150	0301762-3	31,6	0,85	11	12,2	16,7	7	6	25	25
140-160	0301763-1	31,6	0,85	11	12,2	16,7	7	5	25	25
150-170	0301764-0	31,6	0,85	11	12,2	16,7	7	4	25	25
160-180	0301765-8	31,6	0,85	11	12,2	16,7	7	3	25	25
170-190	0301766-6	31,6	0,85	11	12,2	16,7	7	2	10	10
180-200	0301767-4	31,6	0,85	11	12,2	16,7	7	2	10	10
190-210	0301768-2	31,6	0,85	11	12,2	16,7	7	1,8	10	10
200-220	0301769-0	31,6	0,85	11	12,2	16,7	7	1,8	10	10
210-230	0301770-3	31,6	0,85	11	12,2	16,7	7	1,6	10	10
220-240	0301771-1	31,6	0,85	11	12,2	16,7	7	1,6	10	10

* It is recommended to apply 75% of the maximum values contained in the table.

	TECHNICAL INFORMATION	
	MATERIAL	STAINLESS STEEL AISI-316
	FINISH	STAINLESS STEEL
	CORROSION RESISTANCE	1000 HOURS SALT SPRAY (ASTM B-117)
	MAXIMUM TIGHTENING SPEED (RPM)	540 ±5

